

NEW 5 1/8" x 12" GLUE LAM BEAMS BOLTED TOGETHER

HUCQ ?

NOTES - CONTINUED:

YOU SPECIFIED 18" COLUMNS. I COULD NOT FIT/WORK IN THAT NARROW A PASSAGE AND DIG OUT THE DEEP HOLE, SO I WENT WITH 2'.

NOTES:

- 1 COLUMNS POURED (SEE-FRONT VIEW
- 2 AND SECTION VIEW) IN FOUR PLACES AS INDICATED ON YOUR PDF DRAWING OR PLACE NEW COLUMN EVERY ()' SPAN. PURPOSE TO SUPPORT EXISTING FOUNDATION WALL. MINIMIZE/ELIMINATE 3' OFFSET-OF-NEW-RETAING WALL.
- 3 THE REST OF THE DIRT IS DUG OUT FROM UNDER HOUSE. NEW RETAINING WALL- POURED FLUSH WITH NEW COLUM SUPPORTS

NEW CONCRETE FLOOR

NEW CONCRETE FLOOR

NEW CONCRETE FLOOR

NEW FOOTING FOR WALL

1 FRONT COLUMN VIEW

2 SECTION-COLUMN

3 SECTION NEW WALL

DETAIL #1, 2, 3, & 4

SCALE: 3/4" = 1'-0"

FILE: MARK EHRMANN 7455 BLOSSOMWOOD AVENUE, SEBASTOPOL, CA 95472 707-331-0137